



(((((S M O K E))))

WITHOUT
FIRE



Fire Alarm Systems (Conventional)

Common Features

- w Microprocessor Based Panel
- w Resettable Fuse Protection
- w Zone Bypass Feature
- w One man Walk Test Facility
- w Compatible with all types of conventional 12 V detectors
- w Low Battery Warning
- w Installation & Maintenance Friendly
- w AUX 12 V O/P available for 4 wire detectors
- w 230 V AC \pm 10%, 50 Hz operation

Suppression System Features

- w Gas Release Timer (up to 99 sec)
- w Cross Zoning Facility
- w Manual Gas Release with Indication
- w Output to Actuate Solenoid Valve
- w Inbuilt Gas Cylinder
- w Moveable System with Casters

ETDC
TESTED

Models	Fire Detection Systems				Fire Suppression System
	Economy		16x2 Alphanumeric LCD		
Features	FAS-2	FAS-4	FAS-8D	FAS-16D	FSS-2D
Standby Power	12 V DC 4.5 AH	12 V DC 7 AH	12 V DC 7 AH	12 V DC 7 AH	12 V DC 7 AH
Zone I/P	2 Zone	4 Zone	8 Zone	16 Zone	2 Zone
Siren O/P	1	1	1	1	1
Relay O/P	1	1	3	3	3
EOL	1K	1K	2K2	2K2	2K2
Indications	LED + Buzzer	LED + Buzzer	LCD + Buzzer	LCD + Buzzer	LCD + Buzzer
RS 232 / 485	O	O	P	P	P
Dimension (mm)	250x200x90	250x200x90	270x300x100	270x300x100	500x1600x400

MCPs : Fire retardant plastic moulded - Press type resettable.

Smoke Detector : Optical, 12-35 V, 2/4 wire, Remote LED

Note : Specifications subject to change without notice.



- Intrusion Protection
- Fire Protection
- Access Control
- Automatic Gates
- Video Surveillance

Realty Automation & Security Systems Pvt. Ltd.

5, New Sadashiv Peth, Next to Alka Talkies, Pune - 411030, India.
Telfax : 91 20 3092 2630 / 1306 Email : sales@vighnaharta.in http://www.vighnaharta.in