

Vighnaharta Security



Vighnaharta Receiving Unit

Features

- LCD display for various status indication.
- Two telephone line Inputs.
- RS232 port for PC connectivity.
- Fast and error free Communication.
- Audio indication on alert.

Receiving Unit :

Receiving Unit (RU) is a part of sophisticated alert monitoring system. It consists of mainly two hardware units, Communicator (transmitting unit) and RU (Receiving Unit) The RU is placed at the Central Monitoring Station (CMS) and connected to the standard PC. The communication between Vighnaharta Communicator/Communicator +/Mobile Communicator and RU is established via telephone line.



ELECTRICAL:

Power Supply	230V AC + / - 10%. 50 Hz.
Input	Two Telephone Lines.
Output	RS 232 standard serial port
Indication	LED indication for Power on. 16 x 2 LCD display for various statuses. Audio Buzzer indication.

Power Consumption Less than 2W

MECHANICAL DIMENSIONS:

Size (96x192x160) mm(H x W x D)

Weight Less than 1KG.

Operating Temperature 0 to 50°C.

Humidity 5 to 95% Rh.

ENVIRONMENT:

Operating Temperature 0 to 50°C.

Humidity 5 to 95% Rh.

Crystalline Infotek Pvt. Ltd.

Crystal House, 235 Navi Peth, Pune 411 030, India
Telfax: 91 20 433 9634,5 E-mail - nitin@crystalindia.com
www.crystalindia.com