

TrueSafe Manual Call Point

(Family-Fire)

Product Description:

Manual call point is designed for sending an alarm manually after verification of fire or emergency condition exists, by operating the push button the alarm signal can be raised.

This button is a kind of specialism conflagration set used for artificial start in the system of self-motion conflagration. One has to break the glass faceplate of the conflagration button with full strength and the signal will send to the controller. It is for one-time use.



Application:

- Mall
- Complex
- Industries

Product Features:

- Alarm triggering by pressing the black marking or breaking the glass pane
- Protection against injury through a foil-labelled glass pane
- Surface-mounted
- Glass pane design

TS MCP (RED)

TrueSafe Manual Call Point

(Family-Fire)



Specifications

General Specifications	
Current Ratings	30 V DC 2A Maximum
Operating voltage	24 V DC
Alarm Impedance	280Ω, 470Ω
Connections	Terminal - max 2.5 mm 2 Cable
Colour	Red
Mechanical specifications	
Weight	150 gm.
Dimensions	85 x 85 x 50
Housing	ABS
Cable Entry	One (Concealed)
Warranty	One Year

Abbreviations	
TS	TrueSafe
MCP	Manual Call Point

Datasheet version with a date(26/11/2021)



Vighnaharta Technologies Pvt. Ltd.
(formally known as Realty Automation and Security Systems Pvt. Ltd.)
www.vigh www.Vighnaharta.in

Automation | Safety | Security | Surveillance