

Intrusion Sensors

(Family-Intrusion)



Key type panic switch

- Output: NC or NO
- Size: 86 x 86 mm
- Rated load: 250 mA (12 VDC)
- Reset by key



Wireless remote (key fob)

- Operating volt: 12 VDC
- Battery type: 23 A
- RF frequency: 315 or 433.92 MHz
- Transmitting distance: 100 m



Wired door sensor

- Output: NC or NO
- Operating distance: Min. 15 mm, max. 25 mm
- Rated load: 250 mA (12 VDC)
- Weight: 12 g



Vighnaharta Technologies Pvt. Ltd.
(formally known as Realty Automation and Security Systems Pvt. Ltd)
www.vighnaharta.in

Automation | Safety | Security | Surveillance

Intrusion Sensors

(Family-Intrusion)



Wired shutter sensor

- Material: Metal case
- Output: NC
- Operating distance: Min. 35 mm, max. 90 mm
- Rated load: 800 mA (12 VDC)



Wired glass break sensor

- Power supply : Not required
- Output : NC
- Sensor type: Piezoelectric
- Detection range: Radius 180 cm
- Temperature: -20° C to +55° C



Sounder and flash siren

- Power supply: 12 VDC
- Flashing rate: 150 per minute
- Sound level: 110+/-3 (dB/1m)
- Dimension: 122 x 72 x 35 mm



Vighnaharta™

Vighnaharta Technologies Pvt. Ltd.
(formally known as Realty Automation and Security Systems Pvt. Ltd)
www.vighnaharta.in

Automation | Safety | Security | Surveillance

Intrusion Sensors

(Family-Intrusion)



Siren

- Rated voltage : DC 12 V
- Rated current : 320 mA / 600 mA
- Sound level : 105 dB / 110 dB
- Power : 15 W



Steel package resettable panic switch

- Model: SRPS
- Housing: Steel cover with full finish cover
- Mounting: Surface mounts type
- Tamper switch: In built
- Contact rating: 230 VAC/DC, 4 Amp
- Contact output: NO/NC with tamper
- Technology: Micro switch



Resettable panic switch

- Model: RPS
- Housing: 1st grade ABS virgin plastic
- Mounting: Surface mount type
- Tamper switch: NA
- Contact rating: 230 VAC/DC, 10 Amp
- Contact output: NO/NC contact
- Technology: Micro switch



Vighnaharta Technologies Pvt. Ltd.
(formerly known as Realty Automation and Security Systems Pvt. Ltd)
www.vighnaharta.in