

Wired Shutter Magnetic Sensors

Product Description

This magnetic switch is made of heavy-duty solid aluminium die casting body that ensures their longer life. Widely used in numerous industries. These are highly acclaimed for their high performance, easy to use and low maintenance. This switch automatically sense the opening of the shutter and send the signal to the alarm panels in order to restrict unauthorized entry & burglary.



Applications:

- Home, Office & Industrial Security.
- Warehouse/Store room.
- Jeweler Shops etc

Product Features & Specifications:

- Heavy duty solid aluminium dies casting body.
- Wide Operating Gap 35mm-55mm.
- High performance Magnet is used.
- 3ft Long Stainless-Steel Armoured Cable

**Wired Shutter Magnetic Sensors****Specifications**

General Specifications	
Operating Temperature	0°C to 50°C
Colour	Gray
Enclosures	Solid aluminum die casting body
Electrical Specifications	
Power Supply	12 V
Current Rating	800mA
Detection distance	Min 35mm Max 90mm
Mechanical specifications	
Weight	150-200gms
Dimensions	
Display	-
Cable Entry	1ft Long Stainless Steel Armored Cable
Output	N.C.(PFC)
Warranty	
	12 Months from Date of Dispatch for any Manufacturing

Models and Variants	
	Door magnetic contact, concealed door magnetic contact
Abbreviations	
SMCS	Shutter Magnetic Contact Sensor

Datasheet Version with Date(V.2 Oct 2020)